

Classic 3-step Dimming

-LED Spotlight GU10



GU10 5.5W-50W 50lm-250lm-80lm 3-step dimming

GU10 3-step dimming work with any normal toggle wall switch
dimming range 100%-50%-10%, customized dimming range



RA90 LM80



Article Code

TGU10CLA-5.5W-3SLD

GENERAL CHARACTERISTICS

Shape	MR16
Cap - Base	GU10
Rated Wattage	5.5 W
Input Voltage	220-240 Vac
Operating Frequency	50-60 Hz
Lifetime (hours)	25,000 hrs
Switching Cycles	30,000
Start Time from 0% to 100%	< 0.5 s
Power Factor	0.5
Working Temperature	-20°C ~ 40°C
Guarantee	2 years
Dimension	W:50mm x H:53mm

LIGHT CHARACTERISTICS

Color	Warm White / Cold white
Luminous Flux 100%	480 lm
Luminous Flux 50%	250 lm
Luminous Flux 10%	50 lm
Color Temperature	2700 K / 3000 K / 4000 K
Color Rendering Index	Ra90 R9>50
Lamp Efficacy	up to 85 lm/W
Lumen Maintenance Factor	80 %
Beam Angle	38D
Dimming Type	Wall switch
Color Consistency	5 Step MacAdam Ellipse
Wattage Equivalent to Halogen	50W